




AK iTopper
TOPCon Module

570-590W

SK9612TDGDC

Topcon Half-cut Bifacial Dual-Glass Module(16BB)



N-type Topcon technology for lower LCOE

The lower temperature coefficient and better low irradiance performance of Topcon technology can effectively reduce LCOE.



Fire class A, harsh environment adaptability

The back of the dual-glass module adopts high transparent glass, which can adapt to all kinds of harsh environment, and the fire rating can reach Class A.



30-year power warranty

The average life of dual-glass modules is 30 years, 5 years longer than that of single-glass modules.



Double-sided power generation, higher income

The dual-glass module has a double-sided ratio of up to 80% and a power generation gain of 7%-25% on the back side.




LINEAR PERFORMANCE WARRANTY

15
years

Product warranty on materials and workmanship

30
years

Linear power output warranty



CERTIFICATES

ISO 9001: 2015
Quality Management System

IEC 61215 / IEC 61730

ISO 14001: 2015
Environmental Management System

ISO 45001 : 2018
Occupational Health &
Safety Management System

*Certification requirements vary in different markets, please consult with Akcome Optronics sales team for appropriate certification.

570-590W

Topcon 16BB Half-cut Bifacial
Dual-Glass Module



ELECTRICAL PARAMETERS @ STC

	570	575	580	585	590
Max. Power Output Pmax (W)	570	575	580	585	590
Power Tolerance	0~+3%	0~+3%	0~+3%	0~+3%	0~+3%
Max. Power Voltage Vmp (V)	42.29	42.44	42.59	42.68	42.84
Max. Power Current Imp (A)	13.48	13.55	13.62	13.71	13.77
Open Circuit Voltage Voc (V)	51.07	51.27	51.47	51.67	51.87
Short Circuit Current Isc (A)	14.25	14.31	14.37	14.39	14.40
Module Efficiency (%)	22.07	22.26	22.46	22.65	22.84

*STC (Standard Test Condition): Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5
*Measurement Tolerance (±3.0%)

Integrated Power @ (Reference to 580W front)

Power Gains	5%	10%	15%	20%	25%
Max. Power Output Pmax (W)	609	638	667	696	725
Max. Power Voltage Vmp (V)	42.60	42.60	42.59	42.59	42.59
Max. Power Current Imp (A)	14.30	14.98	15.66	16.34	17.03
Open Circuit Voltage Voc (V)	51.47	51.47	52.47	52.47	52.47
Short Circuit Current Isc (A)	15.09	15.81	16.53	17.24	17.96

TEMPERATURE COEFFICIENTS

Temperature Coefficients of Pmp	-0.30%/ °C
Temperature Coefficients of Voc	-0.25%/ °C
Temperature Coefficients of Isc	+0.046%/ °C

MECHANICAL PARAMETERS

Cell Type	Topcon 182x91mm
Number of Cells	144pcs(6x24)
Dimensions (L*W*H)	2278x1134x30mm
Weight	32.5kg
Frame	Anodised Aluminum
Junction Box	IP68, 3 bypass diodes
Cable, Length	4.0mm ² , 300mm

OPERATING CONDITION


Maximum System Voltage(V)	1500(DC)
Operating Temperature(°C)	-40~+85
Max. Wind Load / Snow Load(Pa)	2400/5400
Max. Series Fuse Rating(A)	30
Fire Rating	Class A
Bifaciality	80±5%
NOCT	45 °C

PACKAGE INFORMATION

Container 40'HQ	700pcs
Quantity / Pallet	35pcs
Package size: 2334×1124×1249mm; Net weight: 1137.5kg; Gross weight: 1198.5kg	


Ver: 20230415

ASSEMBLY DRAWING (Unit:mm)



I-V CURVES

Test temperature 25°C



Irradiance: AM1.5, 1000W/m²

